



179.00 EUR
incl. 19% VAT, plus [shipping](#)

Support: [Specifications \[EN\]](#)

- INTEL® 945GSE + ICH7M Chipset
- Support INTEL® Atom N270 CPU(45nm,512K Cache, 1.60 GHz, 533 MHz FSB)
- Build-in INTEL®GMA 950 Graphics Core
- Integrated LVDS support 18-bit TFT LCD
- Supports 1x Gigabit LAN
- Integrated ALC662 HD Audio CODEC with 6-CH
- Support Watch dog Technology
- Support Power on Board
- Mini-ITX Form Factor(170mm x 170mm)

CPU	INTEL®Atom N270 CPU(45nm,512K Cache, 1.60 GHz, 533 MHz FSB)
Chipset	INTEL® 945GSE + ICH7M chipset
Memory	Build-in INTEL® GMA 950 Graphics Core(Share Memory Size: 128/224MB) Front Side Bus 533MHz
Expansion Slots	1 * SO-DIMM Sockets for un-buffered Single Channel DDR2 533/400 SDRAM up to 2 GB
Storage	1 * PCI slot 2 * Serial ATA2 3Gb/s connectors 1 * Ultra DMA 100 / 66 IDE connector
Audio	Realtek ALC662 6-Channel HD Audio CODEC
Ethernet LAN	Realtek RTL8111DL PCI-E Gigabit Ethernet LAN
LVDS	Onboard 18-bit dual channel LVDS connector
USB	Embedded 6 * USB 2.0/1.1
Special Features	Intel Diamond Ville Platform Support ACPI S3 Support CPU Smart FAN Support DC FAN 2 * USB 2.0/1.1 ports 1 * Keyboard connector 1 * RJ-45 port 3 * Audio I/O ports (Line-in, MIC and line-out)
Rear Panel I / O	1 * VGA port 1 * COM port for RS-232 1 * HDTV-OUT 1 * Coaxial out 1 * +12V DC in

Internal I / O

2 * USB 2.0/1.1 headers for 4 USB 2.0 ports
NB / Chassis Fan connectors;
1 * 32-pin LVDS header & 1 * GPIO header
1 * COM header (COM2 for RS-422/485)
1 * AUDIO header
1 * JWDB Pin Header & 1 * Parallel port

BIOS

Award 8MB DIP Flash ROM

Form Factor

Mini ITX Form Factor(170mmx170mm)

Product Accessories

- COM cable
- Manual
- CD
- 2x SATA cable
- I/O shield
- 1x IDE cable
- SATA-Slim ODD Cable+Power